



EPDM Tri-Clamp Gaskets

FEATURES

- Peroxide Cured
- Suitable for SIP and CIP
- Steam Resistance – Very Low Swell and Minimal Loss of Physical Properties After Repeated Steam Cycling
- Chemical Resistance – Very Low Swell and Minimal Loss of Physical Properties After Long-Term Exposure to CIP Media
- Low Extractable Values
- Excellent Dimensional Stability
- Phthalate Free
- Compliant with FDA Regulations CFR 21 177 2600
- Animal Derived Ingredient Free (ADI)
- Laser Engraving Available on Sizes 1"-4"
- USP Class VI Compliant
- Temperature Range: -30°F to 300°F



Part Number	Description
42MPE-1/2	.50in Black EPDM Tri-Clamp Gasket
42MPE-3/4	.75in Black EPDM Tri-Clamp Gasket, Peroxide Cured
40MPE-1	1in Black EPDM Tri-Clamp Gasket, Peroxide Cured
40MPE-1.5	1.5in Black EPDM Tri-Clamp Gasket, Peroxide Cured
40MPE-2	2in Black EPDM Tri-Clamp Gasket, Peroxide Cured
40MPE-2.5	2.5in Black EPDM Tri-Clamp Gasket, Peroxide Cured
40MPE-3	3in Black EPDM Tri-Clamp Gasket, Peroxide Cured
40MPE-4	4in Black EPDM Tri-Clamp Gasket, Peroxide Cured

Coupling Expertise with Speed & Simplicity™