



PTFE Tri-Clamp Gasket

FEATURES

- Excellent Heat Resistance
- Low Absorption Rate
- Good Stability
- Low Extractable Values
- Phthalate Free
- Compliant with FDA Regulations CFR 21 177 2600
- Animal Derived Ingredient Free (ADI)
- Laser Engraving Available on Sizes 1"-4"
- USP Class VI Compliant
- Temperature Range: -100 °F to 500 °F



Part Number	Description
42MPG-1/2	.50in PTFE Tri-Clamp Gasket
42MPG-3/4	.75in PTFE Tri-Clamp Gasket
40MPG-1	1in PTFE Tri-Clamp Gasket
42MPG-1/2	1.5in PTFE Tri-Clamp Gasket
40MPG-2	2in PTFE Tri-Clamp Gasket
40MPG-2.5	2.5in PTFE Tri-Clamp Gasket
40MPG-3	3in PTFE Tri-Clamp Gasket
40MPG-4	4in PTFE Tri-Clamp Gasket
40MOG-5	5in PTFE Tri-Clamp Gasket
40MOG-6	6in PTFE Tri-Clamp Gasket
40MOG-8	8in PTFE Tri-Clamp Gasket
40MOG-10	10in PTFE Tri-Clamp Gasket
40MOG-12	12in PTFE Tri-Clamp Gasket

Coupling Expertise with Speed & Simplicity™