



Tef-Steel Tri-Clamp Gasket

FEATURES

- Tef-Steel Sanitary Gaskets will Maintain I.D. without Re-Torquing or Leaking
- Steam Resistance – Very Low Swell and Minimal Loss of Physical Properties After Repeated Steam Cycling
- Chemical Resistance – Very Low Swell and Minimal Loss of Physical Properties After Long-Term Exposure to CIP Media
- Clean and Easy Removal of Gaskets – No Sticking to the Flanges
- Low Extractable Values
- Excellent Dimensional Stability
- Phthalate Free
- Compliant with FDA Regulations CFR 21 177 2600
- Animal Derived Ingredient Free (ADI)
- Laser Engraving Available on Sizes 1"-4"
- USP Class VI Compliant
- Temperature Range: -300°F to 500°F



| Part Number | Description |
|---------------|----------------------------------|
| 42MPGST-1/2SP | .50in Tef-Steel Tri-Clamp Gasket |
| 42MPGST-3/4SP | .75in Tef-Steel Tri-Clamp Gasket |
| 40MPGST-1SP | 1in Tef-Steel Tri-Clamp Gasket |
| 40MPGST-1.5SP | 1.5in Tef-Steel Tri-Clamp Gasket |
| 40MPGST-2SP | 2in Tef-Steel Tri-Clamp Gasket |
| 40MPGST-2.5SP | 2.5in Tef-Steel Tri-Clamp Gasket |
| 40MPGST-3SP | 3in Tef-Steel Tri-Clamp Gasket |
| 40MPGST-4SP | 4in Tef-Steel Tri-Clamp Gasket |
| 40MOGST-5 | 5in Tef-Steel Tri-Clamp Gasket |
| 40MOGST-6SP | 6in Tef-Steel Tri-Clamp Gasket |
| 40MOGST-8SP | 8in Tef-Steel Tri-Clamp Gasket |
| 40MOGST-10SP | 10in Tef-Steel Tri-Clamp Gasket |
| 40MOGST-12SP | 12in Tef-Steel Tri-Clamp Gasket |

Coupling Expertise with Speed & Simplicity™