



Dry Food Transfer FDF

This FDA grade hose is not suitable for 3-A applications.

Features:

- Extreme Flexibility
- Anti-Static FDA Tube
- Conductive Cover
- Suction & Discharge
- Abrasion Resistant

| MODEL | I.D. | O.D. | WORKING PRESSURE | MIN. BEND RADIUS | WEIGHT PER FT. | VAC. IN HG. | LENGTH |
|--------|------|-------|------------------|------------------|----------------|-------------|--------|
| FDF200 | 2" | 2.64" | 150 PSI | 12.0" | 1.89 lbs | 27" | 130' |
| FDF300 | 3" | 3.66" | 150 PSI | 18.0" | 3.15 lbs | 27" | 130' |
| FDF400 | 4" | 4.72" | 150 PSI | 24.0" | 4.52 lbs | 27" | 130' |

TUBE White, FDA, Anti-Static, NBR

REINFORCEMENT Spiral ply cords w/2 steel helix wires and static wire

RECOMMENDED CLEANING CIP, COP

COVER Green w/conductive black stripe

TEMP. RANGE -15 to 180° F

Applications:

- Flour Transfer
- Railcar Loading/Unloading
- Brewery, Dry Hopping
- Sugar Transfer

This suction and discharge hose, with its anti-static tube and conductive cover, is excellent for wet or dry abrasive materials like sugar or powdered milk. It's designed to be highly flexible and suited for extreme environments.

Coupling Expertise with Speed & Simplicity™