



Beverage Transfer RBT

Features:

- Heavy Duty w/Bounce Back Design
- Non Metallic
- Limited Suction
- Higher Pressure



MODEL	I.D.	O.D.	WORKING PRESSURE	MIN. BEND RADIUS	WEIGHT PER FT.	VAC. IN HG.	LENGTH
RBT100	1"	1.69"	250 PSI	4.0"	.81 lbs	20"	100'
RBT150	1-1/2"	2.23"	250 PSI	5.5"	1.20 lbs.	20"	100'
RBT200	2"	2.92"	250 PSI	6.5"	1.86 lbs.	20"	100'
RBT300	3"	4.09"	250 PSI	10.0"	3.57 lbs.	20"	100'

TUBE White, FDA, 3-A*, EPDM Liner

COVER Purple EPDM w/white stripe

REINFORCEMENT Spiral-plyed synthetic fabric 4 plies 1-1.5"- 6 plies 2" & over

TEMP. RANGE -40 to 225° F

RECOMMENDED CLEANING COP, CIP, SIP (*Consult factory for temperature and duration limitations)

Applications:

- Tank Transfers
- Breweries
- Wineries
- Dairies
- Pump Discharge
- Receiving Bay
- Metal Detection System
- CIP
- Higher Pressure Utility
- High Traffic Areas
- PAA Cleaning Procedures

*PAA should be used as directed by manufacturer

Great for PAA cleaning procedures

**PAA should be used exactly as directed by manufacturer*

A **heavy-duty** discharge hose with **suction capability** is ideal for the highly demanding service of transferring liquid products in breweries, wineries and dairies. (Meets 3-A* standards, USDA requirements and is FDA compliant). **Bounce back design** resists damage from kinking or flattening in high traffic areas.

ALL R-Series hose products meet/comply: USDA Class III requirements, FDA CFR Title 21.1772600, 3-A 18-03

*The 3-A 62-02, standard applies only to assemblies of 3/4" diameter and larger.

WARNING Working pressure ratings for all Flex-Rite™ brand hoses are based on 70° F (ambient temperature). Working pressure and vacuum ratings will decrease as temperatures increase. For "R" series applications that exceed 200° F contact manufacturer for suggestions.

Coupling Expertise with Speed & Simplicity™