



RCR-C & RCR



Features:

- Crush Resistant w/Bounce Back Design
- Positive Grounding (RCR-C)
- High Visibility
- Higher Pressures



Applications:

- Great Food Grade Transfer Hose
- Pump Suction & Discharge
- Receiving Bay
- Metal Detection Systems
- High Traffic
- Wine & Beer Transfer

WARNING Working pressure ratings for all Flex-Rite™ brand hoses are based on 70° F (ambient temperature). Working pressure and vacuum ratings will decrease as temperatures increase. For "R" series applications that exceed 200° F contact manufacturer for suggestions.

MODEL	I.D.	O.D.	WORKING PRESSURE	MIN. BEND RADIUS	WEIGHT PER FT.	VAC. IN HG.	LENGTH
RCR150	1-1/2"	2.11"	250 PSI	4.0"	1.36 lbs	27"	130'
RCR200	2"	2.67"	250 PSI	7.0"	1.87 lbs	27"	130'
RCR250	2-1/2"	3.20"	250 PSI	10.0"	2.48 lbs	27"	130'
RCR300	3"	3.82"	250 PSI	12.0"	3.46 lbs	27"	130'
RCR400	4"	5.08"	250 PSI	15.0"	6.29 lbs	27"	65'

TUBE White, FDA, 3-A*, Chlorobutyl

REINFORCEMENT Spiral-plied synthetic fabric with monofilament helix.

RECOMMENDED CLEANING CIP, COP

COVER Orange EPDM w/white strip

TEMP. RANGE -40 to 250°F

RCR-C150	1-1/2"	2.11"	150 PSI	4.0"	.98 lbs	27"	100'
RCR-C200	2"	2.68"	150 PSI	7.0"	1.38 lbs	27"	100'
RCR-C300	3"	3.85"	150 PSI	12.0"	2.59 lbs	27"	100'

CALL FACTORY FOR 2-2/12" SIZE INFORMATION

TUBE White, FDA, 3-A*, Chlorobutyl

REINFORCEMENT Spiral-plied synthetic fabric with monofilament helix & copper wire

RECOMMENDED CLEANING CIP, COP

COVER Orange EPDM w/white strip

TEMP. RANGE -40 to 250°F

RCR & RCR-C crush resistant hose provides consistent flow whether kinked, twisted or run over. It's designed with a monofilament helix to spring back to its original shape. (Meets 3-A* standards, USDA requirements and is FDA compliant). Excellent for **high traffic areas**, the RCR delivers generous flow rates for wine, beer and other sanitary liquid food stuffs. Bacteria resistant construction delivers taste and odor free flow.

RCR-C has an additional layer of two multi-strand, copper wires to provide positive grounding where static discharge is a concern.

ALL R-Series hose products meet/comply: USDA Class III requirements, FDA CFR Title 21.1772600, 3-A 18-03

*The 3-A 62-02, standard applies only to assemblies of 3/4" diameter and larger.

Coupling Expertise with Speed & Simplicity™