



Now Available RWD

Features:

- FDA Compliant Washdown
- Meets 3A 18-00
- 300 psi
- Chemical Resistant



Applications:

- Washdown
 - Food, Beverage & Dairy
 - Craft Brewing & Spirits
- Sanitizing Transfer
- Meat & Poultry



| MODEL | I.D. | O.D. | WORKING PRESSURE | MIN. BEND RADIUS | WEIGHT PER FT. | VAC. IN HG. | LENGTH |
|----------|------|-------|------------------|------------------|----------------|-------------|--------|
| RWD075 | 3/4" | 1.35" | 300 PSI | - | .41 lbs | - | 200' |
| RWDB075 | 3/4" | 1.35" | 300 PSI | - | .41 lbs | - | 200' |
| RWDBK075 | 3/4" | 1.35" | 300 PSI | - | .41 lbs | - | 200' |
| RWDY075 | 3/4" | 1.35" | 300 PSI | - | .41 lbs | - | 200' |

TUBE White, FDA, 3-A*, EPDM

REINFORCEMENT Spiral-plied synthetic fabric, 4 plies

RECOMMENDED CLEANING CIP, COP

NOTE: EPDM is not recommended for petroleum base fluids.

COVER White, Black, Blue EPDM, Wrapped Finish

TEMP. RANGE -40 to 275° F

Now stocked in White, Blue, Black and Yellow

This **premium** washdown hose is designed for **cleanup duties** in non-oily applications, dairies, creameries, breweries, food, beverage, meat and poultry processing plants. This premium quality hose is capable of handling hot water up to **275° F**. (Meets 3-A* standards, USDA requirements and is FDA compliant). A chemically resistant hose, with a wrapped cover construction designed to provide excellent resistance to cuts and abrasion while providing handling stability.

50 ft. Assemblies:

"Standard assemblies" are fitted with 3/4" male pipe and 1/2" male pipe swivel. **Note:** Other lengths and colors are available.

ALL R-Series hose products meet/comply: USDA Class III requirements, FDA CFR Title 21177.2fi00, 3-A 18-03

WARNING Work pressure ratings for all Flex-Rite® brand hoses are based on 70° F (ambient temperature).

Working pressure and vacuum ratings will decrease as temperatures increase. For "R" series applications that exceed 200°F contact manufacturer for suggestions

Coupling Expertise with Speed & Simplicity™