



Wine & Spirits - Lite

RWS - L

Features:

- Low Friction/Easy Drag
- Highly Flexible
- Wear Resistant
- Full Vacuum
- Easy Clean Up
- Exterior Corrugations allow for draining
- Long Length 130 ft.

Applications:

- Food, Beverage and Dairy
- Craft Brewing, Wine and Spirits
- Tank Hauler/Transport
- Larger Diameter Filling Equipment
- Durable Alternative to PVC
- High Alcohol Suction & Discharge

MODEL	I.D.	O.D.	WORKING PRESSURE	MIN. BEND RADIUS	WEIGHT PER FT.	VAC. IN HG.	LENGTH
RWS-L150	1-1/2"	1.93"	115 PSI	3.0"	.65 lbs	27"	130'
RWS-L200	2"	2.44"	115 PSI	4.0"	.85 lbs	27"	130'
RWS-L250	2-1/2"	2.97"	115 PSI	5.0"	1.15 lbs	27"	130'
RWS-L300	3"	3.46"	115 PSI	6.0"	1.37 lbs	27"	130'

TUBE White, FDA, 3-A*, Chlorobutyl

REINFORCEMENT High strength synthetic cord with steel wire helix

RECOMMENDED CLEANING CIP, COP

COVER Gray Thermoplastic w/white stripe

TEMP. RANGE -40 to 250° F

RWS-L is a lightweight, **Low Force to Bend** hose. The exterior polymer blend with corrugations that are wide and smooth ensures **low friction** and ease of movement. This suction and discharge hose is designed for extra flexibility. **Wear resistance** is achieved by its "ARC" abrasion-resistant cover. **RWS-L** delivers taste and odor-free flow with easy clean up. (Meets 3-A* standards, USDA requirements and FDA compliant).

ALL R-Series hose products meet/comply: USDA Class III requirements, FDA CFR Title 21.1772600, 3-A 18-03

*The 3-A 62-02, standard applies only to assemblies of 3/4" diameter and larger.

WARNING Working pressure ratings for all Flex-Rite™ brand hoses are based on 70° F (ambient temperature). Working pressure and vacuum ratings will decrease as temperatures increase. For "R" series applications that exceed 200° F contact manufacturer for suggestions.

Coupling Expertise with Speed & Simplicity™