



High Purity Silicon

SXD

130 ft. coils

Features:

- Platinum Cured
- Smooth Translucent Silicone
- Lot Traceability
- Phthalates Free
- Easily Placed or Repositioned
- Braid Reinforced
- Lot Number Traceability
- High Temperature Rated
- Ozone/Abrasion Resistant Cover
- Longer Lengths Reduces Scrap

Applications: Packaging:

- Cosmetics
- Pharmaceutical
- Biotech
- Food Products
- 130 ft. Coils
- Pre-cut Lengths
- Custom Assemblies

Certification:

- USP Class VI
- FDR CFR Title 21 - 177.2600
- REACH, 3-A* Compliant
- DM, MHLW, CE
- BSE/TSE
- RoHS

MODEL	I.D.	O.D.	WORKING PRESSURE	MIN. BEND RADIUS	WEIGHT PER FT.	VAC. IN HG.
SXD050	1/2"	1.00"	150 PSI	8.0"	.27 lbs	26
SXD075	3/4"	1.22"	150 PSI	10.0"	.37 lbs	22
SXD100	1"	1.46"	125 PSI	12.0"	.46 lbs	18
SXD150	1-1/2"	1.97"	85 PSI	-	.64 lbs	12
SXD200	2"	2.48"	70 PSI	-	.83 lbs	8
SXD250	2-1/2"	3.01"	60 PSI	-	1.13 lbs	6
SXD300	3"	3.50"	45 PSI	-	1.33 lbs	4

TUBE FDA, 3-A*, USP Class VI silicone - Platinum cured

REINFORCEMENT 4 ply polyester fabric

RECOMMENDED CLEANING CIP, SIP, Autoclave

COVER Translucent (colors available)

TEMP. RANGE -100 to 395° F

LENGTH 130 feet

SXD is specially designed for bulk transfer and high-pressure process applications.

ALL S-Series hose products meet/comply: USDA , USP Class VI requirements, FDA CFR Title 21.1772600, 3-A 18-03

WARNING Working pressure ratings for all Flex-Rite™ brand hoses are based on 70° F (ambient temperature).

Working pressure and vacuum ratings will decrease as temperatures increase. For "S" series applications that exceed 200° F contact manufacturer for suggestions.

Coupling Expertise with Speed & Simplicity™