



High Purity Silicon

SXW

130 ft. coils

Features:

- Platinum Cured
- Smooth Translucent Silicone
- Lot Traceability
- Phthalates Free
- Easily Placed or Repositioned
- Braid Reinforced
- Lot Number Traceability
- High Temperature Rated
- Ozone/Abrasion Resistant Cover
- Longer Lengths Reduces Scrap

Applications: Packaging:

- Cosmetics
- Pharmaceutical
- Biotech
- Food Products
- 130 ft. Coils
- Pre-cut Lengths
- Custom Assemblies

Certification:

- USP Class VI
- FDR CFR Title 21 - 177.2600
- REACH, 3-A* Compliant
- DM, MHLW, CE
- BSE/TSE
- RoHS

MODEL	I.D.	O.D.	WORKING PRESSURE	MIN. BEND RADIUS	WEIGHT PER FT.	VAC. IN HG.
SXW050	1/2"	.94"	150 PSI	1.5"	.31 lbs	29
SXW075	3/4"	1.18"	150 PSI	2.0"	.40 lbs	29
SXW100	1"	1.42"	150 PSI	2.5"	.49 lbs	29
SXW125	1-1/4"	1.71"	137 PSI	3.5"	.65 lbs	29
SXW150	1-1/2"	2.00"	125 PSI	4.5"	.81 lbs	29
SXW200	2"	2.52"	110 PSI	5.5"	1.05 lbs	29
SXW250	2-1/2"	3.09"	85 PSI	7.0"	1.55 lbs	29
SXW300	3"	3.58"	70 PSI	9.0"	1.82 lbs	29
SXW400	4"	4.61"	50 PSI	14.5"	2.38 lbs	29

TUBE FDA, 3-A*, USP Class VI silicone - Platinum cured

REINFORCEMENT 4 ply polyester fabric w/316 L stainless wire helix

RECOMMENDED CLEANING CIP, SIP, Autoclave

COVER Translucent (colors available)

TEMP. RANGE -100 to 395° F

LENGTH 130 feet

SXW with low force-to-bend capabilities is a highly flexible suction, vacuum and delivery hose. Our phthalates free tubes are well suited for pharmaceutical, cosmetic and food products transfer. SXW is reinforced with stainless steel wire to ensure a balance between strength and lightness.

ALL S-Series hose products meet/comply: USDA , USP Class VI requirements, FDA CFR Title 21.1772600, 3-A 18-03

WARNING Working pressure ratings for all Flex-Rite™ brand hoses are based on 70° F (ambient temperature). Working pressure and vacuum ratings will decrease as temperatures increase. For "S" series applications that exceed 200° F contact manufacturer for suggestions.

Coupling Expertise with Speed & Simplicity™