



### Features:

- Crush Resistant w/Bounce Back Design
- Positive Grounding (RCR-C)
- High Visibility
- Higher Pressures



### Applications:

- Great Food Grade Transfer Hose
- Pump Suction & Discharge
- Receiving Bay
- Metal Detection Systems
- High Traffic
- Wine & Beer Transfer

**WARNING** Working pressure ratings for all Flex-Rite™ brand hoses are based on 70° F (ambient temperature). Working pressure and vacuum ratings will decrease as temperatures increase. For "R" series applications that exceed 200° F contact manufacturer for suggestions.

## RCR-C & RCR

MODEL	I.D.	O.D.	WORKING PRESSURE	MIN. BEND RADIUS	WEIGHT PER FT.	VAC. IN HG.	LENGTH
RCR150	1.5"	2.11"	250 PSI	5.9"	0.92 lbs	21"	130'
RCR200	2"	2.68"	250 PSI	8.7"	1.21 lbs	21"	130'
RCR250	2.5"	3.21"	250 PSI	11.8"	1.58 lbs	21"	130'
RCR300	3"	3.82"	250 PSI	13.8"	2.24 lbs	21"	130'
RCR400	4"	5.08"	250 PSI	20.1"	4.09 lbs	21"	65'

**TUBE** White, FDA, 3-A\*, Chlorobutyl

**REINFORCEMENT** Spiral-plyed synthetic fabric with monofilament helix.

**RECOMMENDED CLEANING** CIP, COP

**COVER** Orange EPDM w/white strip

**TEMP. RANGE** -40 to 250°F

RCR-C150	1.5"	2.11"	250 PSI	5.9"	0.92 lbs	21"	130'
RCR-C200	2"	2.68"	250 PSI	8.7"	1.21 lbs	21"	130'
RCR-C300	3"	3.82"	250 PSI	13.8"	2.24 lbs	21"	130'

### CALL FACTORY FOR 2-2/12" SIZE INFORMATION

**TUBE** White, FDA, 3-A\*, Chlorobutyl

**REINFORCEMENT** Spiral-plyed synthetic fabric with monofilament helix & copper wire

**RECOMMENDED CLEANING** CIP, COP

**COVER** Orange EPDM w/white strip

**TEMP. RANGE** -40 to 250°F

**RCR & RCR-C crush resistant** hose provides consistent flow whether kinked, twisted or run over. It's designed with a monofilament helix to spring back to its original shape. (Meets 3-A\* standards, USDA requirements and is FDA compliant). Excellent for **high traffic areas**, the RCR delivers generous flow rates for wine, beer and other sanitary liquid food stuffs. Bacteria resistant construction delivers taste and odor free flow.

**RCR-C** has an additional layer of two multi-strand, copper wires to provide positive grounding where static discharge is a concern.

ALL R-Series hose products meet/comply: USDA Class III requirements, FDA CFR Title 21.1772600, 3-A 18-03  
\*The 3-A 62-02, standard applies only to assemblies of 3/4" diameter and larger.

Coupling Expertise with Speed & Simplicity™